



SSL

Forestry tiller for tractors between 100 and 220 HP with a max working depth of 30 cm.

Standard equipment: gear transmission, PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood.

Options: hydraulic top link, hydraulic support roller for height adjustment.



SSL

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type B+4C/SD
	min	max						
SSL 150	100	160	1000	1450	1930	2080	300	58B+4C/SD
SSL 175	110	160	1000	1690	2170	2260	300	70B+4C/SD
SSL 200	120	220	1000	1930	2420	2620	300	78B+4C/SD
SSL 225	130	220	1000	2170	2650	2810	300	86B+4C/SD
SSL 250	140	220	1000	2410	2890	2990	300	100B+4C/SD

The weight refers to the machine without options.



Rotor type SSL



Tooth type B



Tooth type C/SD



SSM - SSM/HP

Forestry tiller for tractors between 150 and 250 HP with a max working depth of 40 cm.

Standard equipment: double side gear type transmission, PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood. In addition, for the **SSM/HP** model: stronger transmission for tractors up to 300 HP.

Options: hydraulic top link, hydraulic support roller for height adjustment, adjustable dosing blade.



SSM

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type A+C/SD
	min	max						
SSM 200	150	250	1000	2040	2410	3090	400	76A+4C/SD
SSM 225	170	250	1000	2280	2650	3340	400	88A+4C/SD
SSM 250	190	250	1000	2520	2890	3590	400	102A+4C/SD

SSM/HP

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type A+C/SD
	min	max						
SSM/HP 200	150	300	1000	2040	2410	3090	400	76A+4C/SD
SSM/HP 225	170	300	1000	2280	2650	3340	400	88A+4C/SD
SSM/HP 250	190	300	1000	2520	2890	3590	400	102A+4C/SD

The weight refers to the machine without options.



Rotor type SSM



Tooth type A



Tooth type C/SD



SSH

Forestry tiller for tractors between 160 and 350 HP with a max working depth of 50 cm.

Standard equipment: double side gear type transmission, PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood.

Options: hydraulic top link, hydraulic support roller for height adjustment, adjustable dosing blade.



SSH

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type A+C/SD
SSH 150	160	280	1000	1560	1945	3670	500	58A+6C/SD
SSH 175	180	280	1000	1800	2185	3920	500	68A+6C/SD
SSH 200	200	350	1000	2040	2425	4250	500	78A+6C/SD
SSH 225	220	350	1000	2280	2665	4580	500	88A+6C/SD
SSH 250	240	350	1000	2520	2905	4850	500	98A+6C/SD

The weight refers to the machine without options.



Rotor type SSH



Tooth type A



Tooth type C/SD